


### GENERAL INFORMATION

Type	D1EA80M6BB34YY	Efficiency Class	IE1
Pout [kW]	0,55	Vibration Class	A
Speed [rpm]	925	Weight [kg]	
Frame	80M	Degree of Protection	IP55
Current [A]	2,8	Cooling Method	IC 411
cos φ	0,74	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B34
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

						
3~MOT	Type	DM 80-6				
S1	IM B34	IP 55	I.CL.F	IE1		
	V	Hz	A	kW	cos φ	1 / min
Δ	220	50	2,8	0,55	0,74	925
Y	380	50	1,6	0,55	0,74	925
Y	460	60	1,6	0,66	0,73	1110

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
220	100	5,68	2,8	925	550	0,74	65,8	50
220	75	4,15	2,4	950	412,5	0,69	65,15	50
220	50	2,71	2,1	970	275	0,54	64,07	50

Locked Rotor Current	Ia [A]	7,6	Breakdown Torque	Mk [Nm]	12,3
	Ia / In	2,71		Mk / Mn	2,17
Locked Rotor Torque	Ma [Nm]	7,6	No Load Current	[A]	1,3
	Ma / Mn	1,34	No Load Power	[W]	135

### MECHANICAL DATA

DE Bearing	6204-ZZ	Sound Pressure - 50 Hz - dB[B]	77
NDE Bearing	6204-ZZ	Sound Pressure - 60 Hz - dB[B]	78
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Polyamide
Grease Type	-	Cable Entry	PG 11
Feather Key	6*6*32	Cable Gland Position	4
Balance	G 1,6 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
125	35,07	32,03	158,2	-	100	-	32,03	125,07	50	19	M6	40	32	6	21,5
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
6	80	14	159,5	207,5	15	10	306	24	282	-	-	-	-	-	-

