

GENERAL INFORMATION

Type	D2EA100L4BB34YY	Efficiency Class	IE2
Pout [kW]	3	Vibration Class	A
Speed [rpm]	1440	Weight [kg]	
Frame	100L	Degree of Protection	IP55
Current [A]	12,6	Cooling Method	IC 411
cos φ	0,71	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B34
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR		
ONLY ACC. EU REGULATION 640/2009								
3~MOT	Type	DM 100-4						
S1	IM B34	IP 55	I.C.L.F	η%				
	V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ	230	50	12,6	3	0,71	1440	%75	84
Y	400	50	7,3	3	0,71	1440		
Y	480	60	7,3	3,6	0,70	1730	%50	82,2

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	19,9	7,3	1440	3000	0,69	85,5	50
400	75	14,77	6,3	1455	2250	0,61	84	50
400	50	9,79	5,6	1470	1507	0,47	82,2	50

Locked Rotor Current	Ia [A]	42,186	Breakdown Torque	Mk [Nm]	61,23
	Ia / In	3,35		Mk / Mn	3,08
Locked Rotor Torque	Ma [Nm]	52,34	No Load Current	[A]	5,3
	Ma / Mn	2,63	No Load Power	[W]	329

MECHANICAL DATA

DE Bearing	6206-ZZ	Sound Pressure - 50 Hz - dB[B]	78
NDE Bearing	6206-ZZ	Sound Pressure - 60 Hz - dB[B]	81
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Polyamide
Grease Type	-	Cable Entry	PG 11
Feather Key	8*7*50	Cable Gland Position	4
Balance	G 1,6 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
160	46	40	197	-	140	-	40	175	63	28	M10	60	50	8	31
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
7	100	13	199	247	18	12	372,4	22,4	350	-	-	-	-	-	-

