

GENERAL INFORMATION

Type	D2EA160M4AB35	Efficiency Class	IE2
Pout [kW]	11	Vibration Class	A
Speed [rpm]	1475	Weight [kg]	
Frame	160M	Degree of Protection	IP55
Current [A]	22,5	Cooling Method	IC 411
cos φ	0,78	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	DM 160M-4					
S1	IM B35	IP 55	I.C.L.F		η%		IE2 - 89,8
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	22,5	11	0,78	1475	%75	89,6
Δ 480	60	22,5	13,2	0,77	1772	%50	89

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	71,22	22,5	1475	11000	0,78	89,8	50
400	75	53,16	18,5	1482	8250	0,72	89,6	50
400	50	35,2	15,1	1492	5500	0,59	89	50

Locked Rotor Current	Ia [A]	161	Breakdown Torque	Mk [Nm]	240
	Ia / In	7,16		Mk / Mn	3,37
Locked Rotor Torque	Ma [Nm]	206	No Load Current	[A]	12
	Ma / Mn	2,89	No Load Power	[W]	612

MECHANICAL DATA

DE Bearing	6309-ZZ	Sound Pressure - 50 Hz - dB[B]	83
NDE Bearing	6309-ZZ	Sound Pressure - 60 Hz - dB[B]	86
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	12*8*90	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
254	72	51,6	306	-	210	-	51,6	264	108	42	M16	110	90	12	45
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
8	160	22,15	320	396,9	29,8	14,5	601	18,5	582,5	300	250	350	18,5	4	5

