

GENERAL INFORMATION

Type	D2EA180L6AB35YY	Efficiency Class	IE2
Pout [kW]	15	Vibration Class	A
Speed [rpm]	965	Weight [kg]	
Frame	180L	Degree of Protection	IP55
Current [A]	34,8	Cooling Method	IC 411
cos φ	0,69	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	DM 180L-6					
						η%	
S1	IM B35	IP 55	I.C.L.F		IE2 - 89,7		
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	34,8	15	0,69	965	%75	89,8
Δ 480	60	34,8	18	0,65	1160	%50	89,7

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	148,45	34,8	965	15000	0,69	89,7	50
400	75	107,94	27,8	980	11077	0,64	89,8	50
400	50	73,53	16,5	985	7584	0,74	89,7	50

Locked Rotor Current	Ia [A]	191,5	Breakdown Torque	Mk [Nm]	413,5
	Ia / In	5,50		Mk / Mn	2,79
Locked Rotor Torque	Ma [Nm]	178,8	No Load Current	[A]	20,6
	Ma / Mn	1,20	No Load Power	[W]	856

MECHANICAL DATA

DE Bearing	6310-ZZ	Sound Pressure - 50 Hz - dB[B]	87
NDE Bearing	6210-ZZ	Sound Pressure - 60 Hz - dB[B]	90
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	14*9*100	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
279	73,5	64	345	-	279	-	64	329	121	48	M16	110	100	14	51,5
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
9	180	25	357,9	434,8	37,5	14,5	670,5	18,5	652	300	250	350	18,5	4	5

