



GENERAL INFORMATION

Type	D2EA80M4AB34SYY	Efficiency Class	IE2
Pout [kW]	0,75	Vibration Class	A
Speed [rpm]	1435	Weight [kg]	
Frame	80M	Degree of Protection	IP55
Current [A]	3,3	Cooling Method	IC 411
cos φ	0,72	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B34
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE ONLY ACC. EU REGULATION 640/2009							
						3~MOT	Type
S1		IM B34	IP55	I.C.L.F.		η%	
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
230	50	3,4	0,75	0,67	1415	%75	79,5
400	50	2	0,75	0,67	1415		
480	60	2	0,9	0,66	1700	%50	75,2

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	4,97	1,9	1440	750	0,72	79,6	50
400	75	3,7	1,6	1460	565	0,63	80,3	50
400	50	2,46	1,4	1475	380	0,51	77	50

Locked Rotor Current	Ia [A]	15	Breakdown Torque	Mk [Nm]	14,5
	Ia / In	4,55		Mk / Mn	2,92
Locked Rotor Torque	Ma [Nm]	17	No Load Current	[A]	1,3
	Ma / Mn	3,42	No Load Power	[W]	125

MECHANICAL DATA

DE Bearing	6204-ZZ	Sound Pressure - 50 Hz - dB[B]	75
NDE Bearing	6204-ZZ	Sound Pressure - 60 Hz - dB[B]	76
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Polyamide
Grease Type	-	Cable Entry	PG 11
Feather Key	6*6*32	Cable Gland Position	4
Balance	G 1,6 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
125	35,07	32,03	158,2	-	100	-	32,03	125,07	50	19	M6	40	32	6	21,5
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
6	80	14	159,5	207,5	15	10	306	24	282	-	-	-	-	-	-

