

GENERAL INFORMATION

Type	D2EG160M2BB35	Efficiency Class	IE2
Pout [kW]	15	Vibration Class	A
Speed [rpm]	2920	Weight [kg]	
Frame	160M	Degree of Protection	IP55
Current [A]	27	Cooling Method	IC 411
cos φ	0,89	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	DM 160M-2					
S1	IM B35	IP 55	I.C.L.F	η%			
				IE2 - 90,3			
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	27	15	0,89	2920	%75	90,4
Δ 480	60	27	18	0,88	3505	%50	92

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	49,06	27	2920	15000	0,89	90,3	50
400	75	36,3	20,6	2960	11250	0,87	90,4	50
400	50	24,05	14,9	2978	7500	0,79	92	50

Locked Rotor Current	Ia [A]	185	Breakdown Torque	Mk [Nm]	141,2
	Ia / In	6,85		Mk / Mn	2,88
Locked Rotor Torque	Ma [Nm]	130,6	No Load Current	[A]	8,1
	Ma / Mn	2,66	No Load Power	[W]	650

MECHANICAL DATA

DE Bearing	6309-ZZ	Sound Pressure - 50 Hz - dB[B]	93
NDE Bearing	6209-ZZ	Sound Pressure - 60 Hz - dB[B]	96
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	12*8*90	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
254	72,1	52,1	306	-	210	-	52,1	264,2	108	42	M16	110	90	12	45
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
8	160	23	320	396,9	14,5	14,5	604	18,5	585,5	300	250	350	18,5	4	5

