

GENERAL INFORMATION

Type	D2EG180L4AB3YY	Efficiency Class	IE2
Pout [kW]	22	Vibration Class	A
Speed [rpm]	1468	Weight [kg]	
Frame	180L	Degree of Protection	IP55
Current [A]	43,8	Cooling Method	IC 411
cos φ	0,79	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR		
ONLY ACC. EU REGULATION 640/2009								
3~MOT	Type	DM 180-4						
S1	IM B3	IP 55	I.C.L.F	η%				
	V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ	400	50	43,8	22	0,79	1468	%75	90,7
Δ	480	60	43,8	26,4	0,79	1762	%50	89,6

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	143,12	43,8	1468	22000	0,79	91,6	50
400	75	106,76	35,83	1476	16500	0,74	90	50
400	53	70,74	29,4	1485	11000	0,61	88,8	50

Locked Rotor Current	Ia [A]	413	Breakdown Torque	Mk [Nm]	590,7
	Ia / In	9,43		Mk / Mn	4,13
Locked Rotor Torque	Ma [Nm]	329,7	No Load Current	[A]	23,13
	Ma / Mn	2,30	No Load Power	[W]	1015

MECHANICAL DATA

DE Bearing	6310-ZZ	Sound Pressure - 50 Hz - dB[B]	89
NDE Bearing	6210-ZZ	Sound Pressure - 60 Hz - dB[B]	92
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	14*9*100	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
279	72,3	64,5	345	-	279	241	64,5	329	121	48	M16	110	100	14	51,5
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
9	180	25	360	436,9	14,5	14,5	672	-	-	-	-	-	-	-	-

