

### GENERAL INFORMATION

Type	D2EG180M2AB35	Efficiency Class	IE2
Pout [kW]	22	Vibration Class	A
Speed [rpm]	2960	Weight [kg]	
Frame	180M	Degree of Protection	IP55
Current [A]	37	Cooling Method	IC 411
cos φ	0,93	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	DM 180M-2					
S1	IM B35	IP 55	I.C.L.F	η%			
				IE2 - 91,3			
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	37	22	0,93	2960	%75	89,3
Δ 480	60	37	26,4	0,92	3552	%50	84,8

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	70,98	37	2960	22000	0,93	91,3	50
400	75	52,98	27,7	2974	16500	0,96	89,3	50
400	50	35,17	19,2	2987	11000	0,98	84,8	50

  

Locked Rotor Current	Ia [A]	268	Breakdown Torque	Mk [Nm]	205
	Ia / In	7,24		Mk / Mn	2,89
Locked Rotor Torque	Ma [Nm]	163	No Load Current	[A]	7
	Ma / Mn	2,30	No Load Power	[W]	709

### MECHANICAL DATA

DE Bearing	6310-ZZ	Sound Pressure - 50 Hz - dB[B]	93
NDE Bearing	6210-ZZ	Sound Pressure - 60 Hz - dB[B]	96
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	14*9*100	Cable Gland Position	4
Balance	G 2,5 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
279	69	64	345	-	241	279	64	317	121	48	M16	110	100	14	51,5
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
9	180	24	360	436,9	14,5	14,5	658,4	18,5	639,9	300	250	350	18,5	4	5

