

### GENERAL INFORMATION

Type	D2EG200L2AB3	Efficiency Class	IE2
Pout [kW]	30	Vibration Class	A
Speed [rpm]	2970	Weight [kg]	
Frame	200L	Degree of Protection	IP55
Current [A]	52,6	Cooling Method	IC 411
cos φ	0,91	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	DM 200-2					
S1	IM B3	IP 55	I.C.L.F		IE2 - 92		η%
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	52,6	30	0,91	2970	%75	87,2
Δ 480	60	52,6	36	0,9	3564	%50	85,4

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	94,9	55	2970	30000	0,86	92,3	50
400	75	72,28	40,4	2973	22500	0,88	91,1	50
400	50	48,04	28,7	2982	15000	0,84	90,3	50

  

Locked Rotor Current	Ia [A]	423	Breakdown Torque	Mk [Nm]	217,8
	Ia / In	8,04		Mk / Mn	2,30
Locked Rotor Torque	Ma [Nm]	260	No Load Current	[A]	13,5
	Ma / Mn	2,74	No Load Power	[W]	1500

### MECHANICAL DATA

DE Bearing	6312-ZZ	Sound Pressure - 50 Hz - dB[B]	95
NDE Bearing	6212-ZZ	Sound Pressure - 60 Hz - dB[B]	102
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	Optional	DE Shield Material	Cast Iron
Grease Amount	30 gr	Terminal Box Material	Aluminium
Grease Type	POLYREX EM	Cable Entry	M50
Feather Key	16*10*100	Cable Gland Position	4
Balance	G 2,5 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
318	80	68	388	-	305	-	68	355	133	55	M20	110	100	16	59
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
10	200	30	403	487	18,5	18,5	747	-	-	-	-	-	-	-	-

