

### GENERAL INFORMATION

Type	D2EG250M6AB3	Efficiency Class	IE2
Pout [kW]	37	Vibration Class	A
Speed [rpm]	982	Weight [kg]	
Frame	250M	Degree of Protection	IP55
Current [A]	75,2	Cooling Method	IC 411
cos φ	0,78	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	DM 250M-6					
						η%	
						IE2 - 92,2	
S1	IM B3	IP 55	I.C.L.F				
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	75,2	37	0,78	982	%75	91,5
Δ 480	60	75,2	44,4	0,77	1180	%50	91

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	360	75,2	982	37000	0,78	92,2	50
400	75	268	61,4	987	27750	0,71	91,5	50
400	50	178	48,3	991	18500	0,61	91	50

  

Locked Rotor Current	Ia [A]	475	Breakdown Torque	Mk [Nm]	724
	Ia / In	6,32		Mk / Mn	2,01
Locked Rotor Torque	Ma [Nm]	1072	No Load Current	[A]	35
	Ma / Mn	2,98	No Load Power	[W]	1200

### MECHANICAL DATA

DE Bearing	6315-ZZ	Sound Pressure - 50 Hz - dB[B]	90
NDE Bearing	6313-ZZ	Sound Pressure - 60 Hz - dB[B]	93
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	Optional	DE Shield Material	Cast Iron
Grease Amount	30 gr	Terminal Box Material	Aluminium
Grease Type	POLYREX EM	Cable Entry	M50
Feather Key	18*11*125	Cable Gland Position	4
Balance	G 2,5 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
406	82	75	432	-	349	-	75	410	168	65	M20	140	125	18	69
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
11	250	30	466	550	24	24	890,5	-	-	-	-	-	-	-	-

