



GENERAL INFORMATION

Type	D2EG280M4AB35	Efficiency Class	IE2
Pout [kW]	110	Vibration Class	A
Speed [rpm]	1480	Weight [kg]	
Frame	280M	Degree of Protection	IP55
Current [A]	200	Cooling Method	IC 411
cos φ	0,84	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE ONLY ACC. EU REGULATION 640/2009							
						3~MOT	Type
				η%			
S1	IM B35	IP 55	I.C.L.F	IE2 - 94,5			
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	200	110	0,84	1480	%75	95,4
Δ 480	60	200	132	0,84	1775	%50	95,5

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	709,8	200	1480	110000	0,84	94,5	50
400	75	531,27	149	1483	82500	0,84	95,4	50
400	50	352,99	106,8	1488	55000	0,78	95,5	50

Locked Rotor Current	Ia [A]	1220	Breakdown Torque	Mk [Nm]	1590
	Ia / In	6,10		Mk / Mn	2,24
Locked Rotor Torque	Ma [Nm]	1450	No Load Current	[A]	54,9
	Ma / Mn	2,04	No Load Power	[W]	1646

MECHANICAL DATA

DE Bearing	6316-ZZ	Sound Pressure - 50 Hz - dB[B]	101
NDE Bearing	6316-ZZ	Sound Pressure - 60 Hz - dB[B]	104
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	Optional	DE Shield Material	Cast Iron
Grease Amount	30 gr	Terminal Box Material	Aluminium
Grease Type	POLYREX EM	Cable Entry	M50
Feather Key	20*12*125	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
457	120	85	545	-	419	386	85	474	190	75	M20	140	125	20	79,5
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
12	280	40	530	629,9	24	24	970	24	946	500	450	550	18,5	8	5

