



### GENERAL INFORMATION

Type	D2EG315S6AB3	Efficiency Class	IE2
Pout [kW]	75	Vibration Class	A
Speed [rpm]	992	Weight [kg]	
Frame	315S	Degree of Protection	IP55
Current [A]	151,5	Cooling Method	IC 411
cos φ	0,76	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

 USE WITH VARIABLE SPEED DRIVE ONLY ACC. EU REGULATION 640/2009							
				3~MOT	Type	DM 315-6	
S1	IM B3	IP 55	I.C.L.F	η% IE2 - 93,7			
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ 400	50	151,5	75	0,76	992	%75	93,5
Δ 480	60	151,5	90	0,76	1192	%50	93,3
DE	BEARING	GREASE	QUANTITY	CYCLE(HOURS)			
NDE	6318	POLYREX EM	30 GR	4000			
	6318	POLYREX EM	30 GR	4000			

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	722,03	151,5	992	75000	0,76	93,7	50
400	75	540,43	123,1	994	56250	0,71	93,5	50
400	50	359,56	100,2	996	37500	0,58	93,3	50

Locked Rotor Current	Ia [A]	875	Breakdown Torque	Mk [Nm]	1874
	Ia / In	5,78		Mk / Mn	2,60
Locked Rotor Torque	Ma [Nm]	1500	No Load Current	[A]	73,8
	Ma / Mn	2,08	No Load Power	[W]	1964

### MECHANICAL DATA

DE Bearing	6318-ZZ	Sound Pressure - 50 Hz - dB[B]	100
NDE Bearing	6318-ZZ	Sound Pressure - 60 Hz - dB[B]	104
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	YES	DE Shield Material	Cast Iron
Grease Amount	30 gr	Terminal Box Material	Aluminium
Grease Type	POLYREX EM	Cable Entry	M63
Feather Key	22*14*140	Cable Gland Position	4
Balance	G 2,5 Half Key	*Shaft-end diameter (D) is 80 mm for Export Motors.	

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
508	125	115	615	-	406	457	115	550	216	80	M20	170	140	22	85
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
14	315	50	613	817,1	28	28	1156	-	-	-	-	-	-	-	-

