



GENERAL INFORMATION

Type	D3EA100L4BB34	Efficiency Class	IE3
Pout [kW]	3	Vibration Class	A
Speed [rpm]	1445	Weight [kg]	
Frame	100L	Degree of Protection	IP55
Current [A]	12,3	Cooling Method	IC 411
cos φ	0,7	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B34
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

 		3~MOT		Type	DM 100-4			η%	
		S1		IM B34	IP 55	I.C.L.F.		IE3 - 87,7	
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.		
Δ 230	50	12,3	3	0,7	1445	%75	85,3		
Y 400	50	7,1	3	0,7	1445				
Y 460	60	6,1	3	0,71	1735	%50	82,6		
Y 480	60	7,1	3,6	0,71	1733				

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
230	100	19,83	12,3	1445	3000	0,7	87,7	50
230	75	14,72	10,4	1460	2250	0,64	85,3	50
230	50	9,71	9,2	1475	1500	0,5	82,6	50

Locked Rotor Current	Ia [A]	35,5	Breakdown Torque	Mk [Nm]	54
	Ia / In	2,89		Mk / Mn	2,72
Locked Rotor Torque	Ma [Nm]	49,7	No Load Current	[A]	4,65
	Ma / Mn	2,51	No Load Power	[W]	245

MECHANICAL DATA

DE Bearing	6206-ZZ	Sound Pressure - 50 Hz - dB[B]	78
NDE Bearing	6206-ZZ	Sound Pressure - 60 Hz - dB[B]	81
Fixed Bearing	NO	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Polyamide
Grease Type	-	Cable Entry	PG 11
Feather Key	8*7*50	Cable Gland Position	4
Balance	G 1,6 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
160	45,6	40	197	-	140	-	40	174	63	28	M10	60	50	8	31
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
7	100	13	197	245	18	12	425,5	43,7	381,8	-	-	-	-	-	-

