

GENERAL INFORMATION

Type	D3EA160M6AB35	Efficiency Class	IE3
Pout [kW]	7,5	Vibration Class	A
Speed [rpm]	975	Weight [kg]	
Frame	160M	Degree of Protection	IP55
Current [A]	16	Cooling Method	IC 411
cos φ	0,76	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

3~MOT		Type		DM 160M-6				η%	
S1		IM B35		IP 55		I.C.L.F.		IE3 - 89,1	
	V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.	
Δ	400	50	16	7,5	0,76	975	%75	89	
Y	690	50	9,3	7,5	0,76	975			
Δ	460	60	14	7,5	0,73	1181	%50	89,1	
Δ	480	60	16	9	0,75	1178			

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	73,46	16	975	7500	0,76	89,1	50
400	75	54,65	13,2	983	5625	0,69	89	50
400	50	36,17	11	990	3750	0,55	89,1	50

Locked Rotor Current	Ia [A]	110	Breakdown Torque	Mk [Nm]	264
	Ia / In	6,88		Mk / Mn	3,59
Locked Rotor Torque	Ma [Nm]	198	No Load Current	[A]	9,1
	Ma / Mn	2,70	No Load Power	[W]	455

MECHANICAL DATA

DE Bearing	6309-ZZ	Sound Pressure - 50 Hz - dB[B]	84
NDE Bearing	6309-ZZ	Sound Pressure - 60 Hz - dB[B]	87
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	12*8*90	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
254	72	51,6	306	-	210	-	51,6	264	108	42	M16	110	90	12	45
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
8	160	22,15	320	396,9	29,8	14,5	624	18,5	605,5	300	250	350	18,5	4	5

