



### GENERAL INFORMATION

Type	D3EA200L2BB3YY	Efficiency Class	IE3
Pout [kW]	37	Vibration Class	A
Speed [rpm]	2975	Weight [kg]	
Frame	200L	Degree of Protection	IP55
Current [A]	64,7	Cooling Method	IC 411
cos φ	0,88	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

3~MOT		Type		DM 200-2				 	
S1		IM B3		IP 55		I.C.L.F		η%	
								IE3 - 93,7	
	V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.	
Δ	400	50	64,7	37	0,88	2975	%75	92,6	
Y	690	50	37,3	37	0,88	2975			
Δ	460	60	58,2	37	0,88	3575	%50	92,8	
Δ	480	60	64,7	44,4	0,88	3570			

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	118,77	64,7	2975	37000	0,88	93,7	50
400	75	89	50,3	2979	27761	0,86	92,6	50
400	50	59,47	37,17	2986	18593	0,78	92,8	50

Locked Rotor Current	Ia [A]	540	Breakdown Torque	Mk [Nm]	430
	Ia / In	8,35		Mk / Mn	3,62
Locked Rotor Torque	Ma [Nm]	420	No Load Current	[A]	20,6
	Ma / Mn	3,54	No Load Power	[W]	1138

### MECHANICAL DATA

DE Bearing	6312-ZZ	Sound Pressure - 50 Hz - dB[B]	95
NDE Bearing	6212-ZZ	Sound Pressure - 60 Hz - dB[B]	102
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	Optional	DE Shield Material	Cast Iron
Grease Amount	30 gr	Terminal Box Material	Aluminium
Grease Type	POLYREX EM	Cable Entry	M50
Feather Key	16*10*100	Cable Gland Position	4
Balance	G 2,5 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
318	80,1	69,35	388	-	305	-	69,35	357	133	55	M20	110	100	16	59
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
10	200	27	403	487	24	18,5	767	-	-	-	-	-	-	-	-

