

GENERAL INFORMATION

Type	D3EA200L6BB35YY	Efficiency Class	IE3
Pout [kW]	22	Vibration Class	A
Speed [rpm]	980	Weight [kg]	
Frame	200L	Degree of Protection	IP55
Current [A]	47,6	Cooling Method	IC 411
cos φ	0,76	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

3~MOT		Type		DM 200-6			η%	
S1		IM B35		IP 55		I.C.L.F.		IE3 - 92,2
	V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.
Δ	400	50	47,6	22	0,76	980	%75	93,1
Y	690	50	27,5	22	0,76	980		
Δ	460	60	36,6	22	0,74	1175	%50	92,5
Δ	480	60	47,6	25,3	0,77	1170		

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	214,39	47,6	980	22000	0,76	92,2	50
400	75	159,97	39,7	985	16500	0,64	93,1	50
400	50	106,11	33,5	990	11000	0,51	92,5	50

Locked Rotor Current	Ia [A]	300	Breakdown Torque	Mk [Nm]	700
	Ia / In	6,30		Mk / Mn	3,27
Locked Rotor Torque	Ma [Nm]	287	No Load Current	[A]	27,2
	Ma / Mn	1,34	No Load Power	[W]	775

MECHANICAL DATA

DE Bearing	6312-ZZ	Sound Pressure - 50 Hz - dB[B]	87
NDE Bearing	6212-ZZ	Sound Pressure - 60 Hz - dB[B]	90
Fixed Bearing	YES	Housing Material	Aluminium
Lubrication	Optional	DE Shield Material	Cast Iron
Grease Amount	30 gr	Terminal Box Material	Aluminium
Grease Type	POLYREX EM	Cable Entry	M50
Feather Key	16*10*100	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
318	80,1	69,35	388	-	305	-	69,35	357	133	55	M20	110	100	16	59
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
10	200	27	403	487	24	18,5	767	20	747	350	300	400	18,5	4	5

