



GENERAL INFORMATION

Type	D3EG160L6AB35	Efficiency Class	IE3
Pout [kW]	11	Vibration Class	A
Speed [rpm]	975	Weight [kg]	
Frame	160L	Degree of Protection	IP55
Current [A]	23,6	Cooling Method	IC 411
cos φ	0,74	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

 		3~MOT		Type	DM 160L-6		η%	
						IE3 - 90		
S1		IM B35		IP 55		I.C.L.F.		
V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.	
Δ 400	50	23,6	11	0,74	975	%75	91,8	
Y 690	50	13,6	11	0,74	975			
Δ 460	60	20,3	11	0,74	1175	%50	88,9	
Δ 480	60	23,6	13,2	0,74	1173			

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	107,74	23,6	975	11000	0,74	90	50
400	75	80,4	19,8	980	8250	0,66	91,8	50
400	50	53,22	17,2	987	5500	0,52	88,9	50

Locked Rotor Current	Ia [A]	165	Breakdown Torque	Mk [Nm]	403
	Ia / In	6,99		Mk / Mn	3,74
Locked Rotor Torque	Ma [Nm]	314,5	No Load Current	[A]	14,4
	Ma / Mn	2,92	No Load Power	[W]	600

MECHANICAL DATA

DE Bearing	6309-ZZ	Sound Pressure - 50 Hz - dB[B]	84
NDE Bearing	6209-ZZ	Sound Pressure - 60 Hz - dB[B]	87
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	12*8*90	Cable Gland Position	4
Balance	G 2,5 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
254	72	52,1	306	-	254	-	52,1	308,2	108	42	M16	110	90	12	45
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
8	160	23	320	396,9	14,5	14,5	682	18,5	663,5	300	250	350	18,5	4	5

