



### GENERAL INFORMATION

Type	D3EG160M2BB35	Efficiency Class	IE3
Pout [kW]	15	Vibration Class	A
Speed [rpm]	2970	Weight [kg]	
Frame	160M	Degree of Protection	IP55
Current [A]	26,3	Cooling Method	IC 411
cos φ	0,89	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

 		3~MOT		Type	DM 160M-2			η%	
		S1	IM B35	IP 55	I.C.L.F.		IE3 - 91,9		
	V	Hz	A	kW	cos φ	1 / min	LOAD	EFF.	
Δ	400	50	26,3	15	0,89	2970	%75	91,6	
Y	690	50	15,2	15	0,89	2970			
Δ	460	60	22,8	15	0,88	3576	%50	91,3	
Δ	480	60	26,3	18	0,89	3572			

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	48,23	26,3	2970	15000	0,89	91,9	50
400	75	36,04	20,2	2981	11250	0,88	91,6	50
400	50	23,94	14,9	2992	7500	0,8	91,3	50

Locked Rotor Current	Ia [A]	260	Breakdown Torque	Mk [Nm]	202
	Ia / In	9,89		Mk / Mn	4,19
Locked Rotor Torque	Ma [Nm]	200	No Load Current	[A]	8,5
	Ma / Mn	4,15	No Load Power	[W]	630

### MECHANICAL DATA

DE Bearing	6309-ZZ	Sound Pressure - 50 Hz - dB[B]	93
NDE Bearing	6209-ZZ	Sound Pressure - 60 Hz - dB[B]	96
Fixed Bearing	YES	Housing Material	Cast Iron
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Aluminium
Grease Type	-	Cable Entry	M32
Feather Key	12*8*90	Cable Gland Position	4
Balance	G 2,5 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
254	72,1	52,1	306	-	210	-	52,1	264,2	108	42	M16	110	90	12	45
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
8	160	23	320	396,9	14,5	14,5	634	18,5	615,5	300	250	350	18,5	4	5

