


GENERAL INFORMATION

Type	DSSA100L4AB3	Efficiency Class	-
Pout [kW]	2,2	Vibration Class	A
Speed [rpm]	1430	Weight [kg]	
Frame	100L	Degree of Protection	IP55
Current [A]	14,2	Cooling Method	IC 411
cos φ	0,93	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000
Run [μf]	50	Start [μf]	280-333

					
1~MOT	Type	DM 100-4			
S1	IM B3	IP 55	I.C.L.F		
V	Hz	A	kW	cos φ	1 / min
220	50	14,2	2,2	0,93	1430
CAPACITOR 50 μF 450 V / 280-333 μF 250 V					

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
220	100	14,69	14,2	1430	2200	0,93	78	50
Locked Rotor Current	Ia [A]	58,6	Breakdown Torque	Mk [Nm]	30,5			
	Ia / In	4,13		Mk / Mn	2,08			
Locked Rotor Torque	Ma [Nm]	36,3	No Load Current	[A]	9			
	Ma / Mn	2,47	No Load Power	[W]	453			

MECHANICAL DATA

DE Bearing	6206-ZZ	Sound Pressure - 50 Hz - dB[B]	75
NDE Bearing	6204-ZZ	Sound Pressure - 60 Hz - dB[B]	76
Fixed Bearing	NO	Housing Material	Aluminium
Lubrication	-	DE Shield Material	Aluminium
Grease Amount	-	Terminal Box Material	Polyamide
Grease Type	-	Cable Entry	PG 11
Feather Key	8*7*50	Cable Gland Position	4
Balance	G 1,6 Half Key		

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
160	45,6	40	197	177,5	140	-	40	174	63	28	M10	60	50	8	31
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
7	100	13	187	250,5	18	12	371,5	-	-	-	-	-	-	-	-

