


GENERAL INFORMATION

Type	DSSA100L4AB35	Efficiency Class	-
Pout [kW]	2,2	Vibration Class	A
Speed [rpm]	1430	Weight [kg]	
Frame	100L	Degree of Protection	IP55
Current [A]	14,2	Cooling Method	IC 411
cos φ	0,93	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000
Run [μf]	50	Start [μf]	280-333

					
1~MOT	Type	DM 100-4			
S1	IM B35	IP 55	I.C.L.F		
V	Hz	A	kW	cos φ	1 / min
220	50	14,2	2,2	0,93	1430
CAPACITOR 50 μf 450 V / 280-333 μf 250 V					

ELECTRICAL DATA (RAW MEASUREMENT DATA)

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
220	100	14,69	14,2	1430	2200	0,93	78	50
Locked Rotor Current	Ia [A]	58,6		Breakdown Torque	Mk [Nm]	30,5		
	Ia / In	4,13			Mk / Mn	2,08		
Locked Rotor Torque	Ma [Nm]	36,3		No Load Current	[A]	9		
	Ma / Mn	2,47		No Load Power	[W]	453		

MECHANICAL DATA

DE Bearing	6206-ZZ	Sound Pressure - 50 Hz - dB[B]	75	Cable Gland Position	
NDE Bearing	6204-ZZ	Sound Pressure - 60 Hz - dB[B]	76		
Fixed Bearing	NO	Housing Material	Aluminium		
Lubrication	-	DE Shield Material	Aluminium		
Grease Amount	-	Terminal Box Material	Polyamide		
Grease Type	-	Cable Entry	PG 11		
Feather Key	8*7*50	Cable Gland Position	4		
Balance	G 1,6 Half Key				

MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
160	45,6	40	197	177,5	140	-	40	174	63	28	M10	60	50	8	31
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
7	100	13	187	250,5	18	12	371,5	13	358,5	215	180	250	14,5	4	4

