



### GENERAL INFORMATION

Type	DSSA71M2DB3	Efficiency Class	-
Pout [kW]	0,55	Vibration Class	A
Speed [rpm]	2830	Weight [kg]	
Frame	71M	Degree of Protection	IP55
Current [A]	4	Cooling Method	IC 411
cos φ	0,91	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000
Run [μf]	20	Start [μf]	124-149

 					
1~MOT	Type	DM 71-2			
S1	IM B3	IP 55	I.C.L.F		
V	Hz	A	kW	cos φ	1 / min
220	50	4	0,55	0,91	2830
CAPACITOR 20 μf 450 V / 124-149 μf 250 V					

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
220	100	1,86	4	2830	550	0,91	70	50
Locked Rotor Current	Ia [A]	19,8	Breakdown Torque	Mk [Nm]	5,3			
	Ia / In	4,95		Mk / Mn	2,86			
Locked Rotor Torque	Ma [Nm]	2,5	No Load Current	[A]	1,7			
	Ma / Mn	1,35	No Load Power	[W]	260			

### MECHANICAL DATA

DE Bearing	6202-ZZ	Sound Pressure - 50 Hz - dB[B]	80	Cable Gland Position
NDE Bearing	6202-ZZ	Sound Pressure - 60 Hz - dB[B]	87	
Fixed Bearing	NO	Housing Material	Aluminium	
Lubrication	-	DE Shield Material	Aluminium	
Grease Amount	-	Terminal Box Material	Polyamide	
Grease Type	-	Cable Entry	PG 11	
Feather Key	5*5*22	Cable Gland Position	4	
Balance	G 1,6 Half Key			

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
112	30,1	23,5	139,6	150	90	-	23,5	108	45	14	M5	30	22	5	16
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
5	71	9,5	128,75	175,25	11	7	247,5	-	-	-	-	-	-	-	-

