


### GENERAL INFORMATION

Type	DSSA71M4CB35	Efficiency Class	-
Pout [kW]	0,37	Vibration Class	A
Speed [rpm]	1320	Weight [kg]	
Frame	71M	Degree of Protection	IP55
Current [A]	3,3	Cooling Method	IC 411
cos φ	0,89	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B35
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000
Run [μf]	15	Start [μf]	64-77

					
1~MOT	Type	DM C 71-4			
S1	IM B35	IP 55	I.C.L.F		
V	Hz	A	kW	cos φ	1 / min
220	50	3,3	0,37	0,89	1320
CAPACITOR 15 μF 450 V / 64-77 μF 250 V					

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
220	100	2,68	3,3	1320	370	0,89	65	50
Locked Rotor Current	Ia [A]	12,7	Breakdown Torque	Mk [Nm]	8,2			
	Ia / In	3,85		Mk / Mn	3,06			
Locked Rotor Torque	Ma [Nm]	6,9	No Load Current	[A]	1,86			
	Ma / Mn	2,58	No Load Power	[W]	184,7			

### MECHANICAL DATA

DE Bearing	6202-ZZ	Sound Pressure - 50 Hz - dB[B]	75	Cable Gland Position
NDE Bearing	6202-ZZ	Sound Pressure - 60 Hz - dB[B]	76	
Fixed Bearing	NO	Housing Material	Aluminium	
Lubrication	-	DE Shield Material	Aluminium	
Grease Amount	-	Terminal Box Material	Polyamide	
Grease Type	-	Cable Entry	PG 11	
Feather Key	5*5*22	Cable Gland Position	4	
Balance	G 1,6 Half Key			

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
112	30,1	23,5	139,6	150	90	-	23,5	108	45	14	M5	30	22	5	16
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
5	71	9,5	128,75	175,25	11	7	247,5	8,7	238,8	130	110	160	10	4	3,5

