

### GENERAL INFORMATION

Type	V2EG132S2BB3	Efficiency Class	IE2
Pout [kW]	7,5	Vibration Class	A
Speed [rpm]	2930	Weight [kg]	
Frame	132S	Degree of Protection	IP55
Current [A]	13,3	Cooling Method	IC 411
cos φ	0,9	Insulation Class	F
Rotation	CW-CCW	Temperature Class	B
Duty	S1	Construction	IM B3
Ambient Temp. [°C]	-20...+40	Altitude above sea [m]	1000

USE WITH VARIABLE SPEED DRIVE		CE		TS		QR	
ONLY ACC. EU REGULATION 640/2009							
3~MOT	Type	VM 132S-2					
S1	IM B3	IP 55	I.C.L.F		η%		
	V	Hz	A	kW	cos φ	1 / min	LOAD
Δ	400	50	13,3	7,5	0,9	2930	%75
Δ	480	60	13,3	9	0,89	3530	%50
							EFF.
							88,1
							85,2

### ELECTRICAL DATA ( RAW MEASUREMENT DATA )

V1	%Load	T [Nm]	I [A]	rpm	P2 [W]	cos φ	Efficiency	Hz
400	100	24,45	13,3	2930	7500	0,9	88,1	50
400	75	18,23	10,6	2946	5625	0,87	88,1	50
400	50	12,07	7,9	2968	3750	0,8	85,2	50

  

Locked Rotor Current	Ia [A]	110	Breakdown Torque	Mk [Nm]	92
	Ia / In	8,27		Mk / Mn	3,76
Locked Rotor Torque	Ma [Nm]	80	No Load Current	[A]	4,4
	Ma / Mn	3,27	No Load Power	[W]	375

### MECHANICAL DATA

DE Bearing	6208-ZZ	Sound Pressure - 50 Hz - dB[B]	90
NDE Bearing	6208-ZZ	Sound Pressure - 60 Hz - dB[B]	93
Fixed Bearing	NO	Housing Material	Cast Iron
Lubrication	-	DE Shield Material	Cast Iron
Grease Amount	-	Terminal Box Material	Polyamide
Grease Type	-	Cable Entry	PG 21
Feather Key	10*8*70	Cable Gland Position	4
Balance	G 1,6 Half Key		

### MECHANICAL DIMENSIONS

A	AA	AB	AC	AD	B	B'	BA	BB	C	D	d	E	EB	F	GA
216	58,5	37,1	258,5	-	140	-	37,1	180,2	89	38	M12	80	70	10	41
GD	H	HA	HC	HD	K	K1	L	LA	LB	M	N	P	S	S1	T
8	132	17,5	263,5	317,5	12	12	452	-	-	-	-	-	-	-	-

